

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 000000002050003769 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : PM 2P93 UV Fill-R Grey 0,4L

Product code : 000000002050003769

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Coatings and related products

1.3 Details of the supplier of the safety data sheet

Company:

BASF Coatings France SAS
Z.I de Breuil-Le-Sec, Rue André Pomery
60480 Breuil-Le-Sec
France

Contact address:

BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
United Kingdom

Telephone: +44 161 475 3000

E-mail address: product-safety-uk-and-ireland@basf.com

1.4 Emergency telephone

International emergency number:

Telephone: +49 180 2273-112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Aerosols, Category 1

Eye irritation, Category 2

Skin sensitization, Category 1

Long-term (chronic) aquatic hazard, Category 2

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758




We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 0000000020500037 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025
69

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
Precautionary Statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection/ face protection. Response: P391 Collect spillage. Storage: P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous ingredients which must be listed on the label:

tripropylene glycol diacrylate
(OLIGOMER) 4,4'-Isopropylidenediphenol, oligomeric reactionproducts with 1-chloro-2,3-epoxypropane, esters with acrylic acid
Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-
Neopentyl glycol, propoxylated, esters with acrylic acid
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction
Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2-

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 0000000020500037 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025
69

Container is under pressure. Protect from sun and temperatures above 50 °C. Do not open with force or incinerate even after use. Do not spray into flames or onto glowing objects.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : unsaturated acrylic resin fillers
organic solvent
pigment
inorganic compounds
organic compounds

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
polymeric urethane acrylate	123904-10-9	Skin Irrit. 2; H315 Eye Irrit. 2; H319	>= 7 - < 10
acetone	67-64-1 200-662-2 606-001-00-8 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 7 - < 10
n-Butyl acetate	123-86-4 204-658-1 607-025-00-1 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 5 - < 7
Methylethylketone	78-93-3 201-159-0 606-002-00-3 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 3 - < 5

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 0000000020500037 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025
69

tripropylene glycol diacrylate	42978-66-5 256-032-2 607-249-00-X UK-20-0537843089-5-0000	Eye Irrit. 2; H319 Skin Sens. 1A; H317 STOT SE 3; H335 (Respiratory system) Aquatic Chronic 2; H411 specific concentration limit STOT SE 3; H335 >= 10 %	>= 3 - < 5
(OLIGOMER) 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	55818-57-0 500-130-2	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 2.5 - < 3
Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-	162881-26-7 423-340-5 015-189-00-5 UK-20-0537843089-5-0000	Skin Sens. 1A; H317 Aquatic Chronic 4; H413	>= 2 - < 2.5
Neopentyl glycol, propoxylated, esters with acrylic acid	84170-74-1 01-2119970213-43	Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 1 - < 2
zinc phosphate	7779-90-0 231-944-3 030-011-00-6 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 1 - < 2
2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction	1187441-10-6	Eye Dam. 1; H318 Skin Sens. 1; H317	>= 0.5 - < 1
Poly(oxy-1,2-ethanediyl), .alpha.-hydro-.omega.-[(1-oxo-2- p	28961-43-5 500-066-5 01-2119489900-30	Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 0.5 - < 1
Substances with a workplace exposure limit :			
dimethyl ether	115-10-6 204-065-8 603-019-00-8 UK-20-9702550300-0-0000 UK-20-0537843089-	Flam. Gas 1A; H220 Press. Gas Liquefied gas; H280	>= 25 - < 50

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 0000000020500037 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025
69

	5-0000		
talc	14807-96-6 238-877-9 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000		$\geq 5 - < 7$
Kaolin	1332-58-7 310-194-1		$\geq 3 - < 5$
Silicon dioxide	7631-86-9 231-545-4 UK-20-2749242067-7-0000 UK-20-9702550300-0-0000 UK-20-0537843089-5-0000 UK-20-9642318150-0-0000		$\geq 1 - < 2$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.
Move out of dangerous area.
In all cases of doubt, or when symptoms persist, seek medical attention.
Immediately remove contaminated clothing.
If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).
First aid personnel should pay attention to their own safety.
- If inhaled : If breathed in, move person into fresh air.
If breathing is irregular or stopped, administer artificial respiration.
If symptoms persist, call a physician.
- In case of skin contact : In case of skin contact avoid direct exposure to sunlight or other UV radiation since this would increase sensitisation of the skin.
If symptoms persist, call a physician.
Wash off immediately with soap and plenty of water while

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.0	13.10.2025	0000000020500037	Date of first issue: 31.03.2025
		69	

-
- removing all contaminated clothes and shoes.
Do NOT use solvents or thinners.
- In case of eye contact : Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
Call a physician immediately.
If easy to do, remove contact lens, if worn.
In case of accidental eye contact avoid concurrent exposure to the sun or other sources of UV light which may increase the sensitivity of eye.
- If swallowed : Rinse mouth.
Do NOT induce vomiting.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
- Risks : May cause an allergic skin reaction.
Causes serious eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No known specific antidote.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Water spray jet
Dry powder
Alcohol-resistant foam
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire : Cool containers exposed to fire with water. Decomposition,

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.0	13.10.2025	0000000020500037 69	Date of first issue: 31.03.2025

fighting : pressure build-up and bursting of containers may occur.

Hazardous combustion products : Carbon oxides
Oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : Cool containers/tanks with water spray.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Avoid breathing vapours.
For non-emergency personnel:
Use personal protective equipment.
Ensure adequate ventilation, especially in confined areas.
Keep away from sources of ignition.
For emergency responders:
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
Avoid subsoil penetration.
Do not allow uncontrolled discharge of product into the environment.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ensure adequate ventilation.
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal considerations see section 13.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.0	13.10.2025	0000000020500037	Date of first issue: 31.03.2025
		69	

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).
Do not return residues to the storage containers.
Handle with care - avoid bumps, friction and impact.
Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.
The workplace should be equipped with an emergency shower and eye-rinsing facility.
Avoid contact with the skin, eyes and clothing.
Handle in accordance with good industrial hygiene and safety practice.
- Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment. Vapors may form explosive mixtures with air.
- Hygiene measures : Remove contaminated clothing immediately and dispose of safely.
Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

- Further information on storage conditions : Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Keep in a dry, cool and well-ventilated place.
- Advice on common storage : Keep away from free radical initiators, peroxides, strong alkalis and reactive materials to avoid exothermic polymerization.
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Packaging material : Suitable material: Aluminium

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 0000000020500037 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025
69

Suitable material: Stove-lacquer R 78433, Stove-lacquer EHD0022, Stove-lacquer RDL 50, Stove-lacquer C222A/C221A, Stove-lacquer 79/14/3 (Müller/CH), Standard interior paint, Stove-lacquer Vitalure 745, Stove-lacquer Valspar HXR008F red, Stove-lacquer KNS L-5X

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dimethyl ether	115-10-6	TWA	400 ppm 766 mg/m ³	GB EH40
		STEL	500 ppm 958 mg/m ³	GB EH40
		TWA	1,000 ppm 1,920 mg/m ³	2000/39/EC
Further information: Indicative				
acetone	67-64-1	TWA	500 ppm 1,210 mg/m ³	GB EH40
		STEL	1,500 ppm 3,620 mg/m ³	GB EH40
		TWA	500 ppm 1,210 mg/m ³	2000/39/EC
Further information: Indicative				
talc	14807-96-6	TWA (Respirable dust)	1 mg/m ³	GB EH40
n-Butyl acetate	123-86-4	TWA	150 ppm 724 mg/m ³	GB EH40
		STEL	200 ppm 966 mg/m ³	GB EH40
		STEL	150 ppm 723 mg/m ³	2019/1831/EU
Further information: Indicative				
		TWA	50 ppm 241 mg/m ³	2019/1831/EU
Further information: Indicative				
Methylethylketone	78-93-3	TWA	200 ppm 600 mg/m ³	GB EH40
Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will				

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 0000000020500037 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025
69

		lead to systemic toxicity.		
		STEL	300 ppm 899 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	300 ppm 900 mg/m ³	2000/39/EC
		Further information: Indicative		
		TWA	200 ppm 600 mg/m ³	2000/39/EC
		Further information: Indicative		
Kaolin	1332-58-7	TWA (Respirable dust)	2 mg/m ³	GB EH40
Silicon dioxide	7631-86-9	TWA (inhalable dust)	6 mg/m ³ (Silica)	GB EH40
		TWA (Respirable dust)	2.4 mg/m ³ (Silica)	GB EH40

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Methylethylketone	78-93-3	butan-2-one: 70 micromol per litre (Urine)	After shift	GB EH40 BAT

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Required when there is a risk of eye contact.
Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Hand protection

Remarks : Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. nitrile gloves - material thickness: 0,35 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degrada-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.0	13.10.2025	0000000020500037	Date of first issue: 31.03.2025

69

tion or chemical breakthrough. Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)

Preventive skin protection

Skin and body protection : Wear chemical-resistant disposable coverall and boots. Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.

Respiratory protection : Suitable respiratory equipment: half-mask with A1P2 class combination filter
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Protective measures : Eye wash fountains and safety showers must be easily accessible.

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.

Avoid contact with the skin, eyes and clothing.
Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: aerosol
Color	: gray
Odor	: ether-like
pH	: substance/mixture is a gas
Melting point/ range	: Study technically not feasible.
Boiling point/boiling range	: Study technically not feasible.
Flash point	: -12 °C Method: ISO 3679 Flash point is only valid for liquid portion in the aerosol can.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.0	13.10.2025	0000000020500037	Date of first issue: 31.03.2025
		69	

Evaporation rate	:	not determined
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Vapor pressure	:	203.0 hPa (20 °C) 682.0 hPa (50 °C)
Relative density	:	No data available
Density	:	1.216 g/cm ³ (20 °C)
Solubility(ies)	:	
Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity	:	
Viscosity, kinematic	:	36.0 mm ² /s (23 °C) not determined (40 °C)
Flow time	:	31 s at 23 °C Cross section: 4 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Self-heating substances	:	The substance or mixture is not classified as self heating.
Metal corrosion rate	:	Not corrosive to metals.
Particle size	:	No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version	Revision Date:	SDS Number:	Date of last issue: 23.08.2025
3.0	13.10.2025	0000000020500037 69	Date of first issue: 31.03.2025

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.
Risk of bursting.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.

Ultraviolet rays
Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Keep away from free radical initiators, peroxides, strong alkalis and reactive materials to avoid exothermic polymerization.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Components:

acetone:

Assessment : Repeated exposure may cause skin dryness or cracking.

n-Butyl acetate:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 0000000020500037 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025
69

Assessment : Repeated exposure may cause skin dryness or cracking.

Methylethylketone:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration toxicity

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Components:

zinc phosphate:

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 0000000020500037 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025
69

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

acetone:

Partition coefficient: n-octanol/water : log Pow: -0.24 (25 °C)

n-Butyl acetate:

Partition coefficient: n-octanol/water : Pow: 200 (25 °C)
log Pow: 2.3 (25 °C)
pH: 7
Method: OECD Test Guideline 117
GLP: yes

Methylethylketone:

Partition coefficient: n-octanol/water : log Pow: 0.29
GLP: No information available.
Remarks: Information taken from reference works and the literature.

tripropylene glycol diacrylate:

Partition coefficient: n-octanol/water : log Pow: 2.0 (25 °C)
GLP: no

log Pow: 2 (25 °C)
Method: OECD Test Guideline 117
GLP: yes

log Pow: 2.77 (25 °C)
Method: OECD Test Guideline 117
GLP: yes

log Pow: 2.1 (25 °C)
Method: OECD Test Guideline 117
GLP: yes

log Pow: 2.5 - 2.7 (23 °C)
pH: 6.7
Method: OECD Test Guideline 117
GLP: yes

(OLIGOMER) 4,4'-Isopropylidenediphenol, oligomeric reactionproducts with 1-chloro-2,3-epoxypropane, esters with acrylic acid:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 0000000020500037 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025
69

Partition coefficient: n-octanol/water : log Pow: ca. 1.6 - 3.8 (23 °C)
Method: OECD Test Guideline 117
GLP: yes

log Pow: 1.6 - 3.8 (23 °C)
pH: 6.4
Method: OECD Test Guideline 117
GLP: yes

log Pow: 1.6 - 3 (23 °C)
pH: 6.4
Method: OECD Test Guideline 117
GLP: yes

log Pow: 3 - 3.8 (23 °C)
pH: 6.4
Method: OECD Test Guideline 117
GLP: yes

Phosphine oxide, phenylbis(2,4,6-trimethylbenzoyl)-:

Partition coefficient: n-octanol/water : log Pow: 5.8 (22 °C)
pH: 8.3
Method: OECD Test Guideline 117
GLP: yes

2-Propenoic acid, 2-methyl-, 2-hydroxyethyl ester, reaction:

Partition coefficient: n-octanol/water : Pow: 2 - 5,200 (23.3 °C)
log Pow: 0.3 - 3.7 (23.3 °C)
Method: OECD Test Guideline 117
GLP: yes

Poly(oxy-1,2-ethanediyl), .alpha.-hydro.-omega.-[(1-oxo-2- p:

Partition coefficient: n-octanol/water : log Pow: 2.89 (23 °C)
pH: 8.1
Method: OECD Test Guideline 107
GLP: no

dimethyl ether:

Partition coefficient: n-octanol/water : log Pow: 0.07 (25 °C)
pH: 7

talc:

Partition coefficient: n-octanol/water : log Pow: -9.4 (25 °C)
pH: 7

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 0000000020500037 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025
69

GLP: no

Silicon dioxide:

Partition coefficient: n-octanol/water : Remarks: Not applicable

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 0000000020500037 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025
69

IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
(ZINC PHOSPHATE, TRIPROPYLENEGLYCOL DIACRYLATE)
IATA : AEROSOLS

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 2	2.1
ADR	: 2	2.1
RID	: 2	2.1
IMDG	: 2.1	
IATA	: 2.1	

14.4 Packing group

ADN
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)
Packing instruction (cargo) : 203

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 0000000020500037 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025
69

aircraft)
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable gas

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17) : Conditions of restriction for the following entries should be considered:
Number on list 72, 3

Number on list 3

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 0000000020500037 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025
69

UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation : Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) : Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable
Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : acetone
UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH) P3a FLAMMABLE AEROSOLS
E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Volatile organic compounds (VOC) content: 775.07 g/l
VOC content excluding water

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information

Full text of H-Statements

H220 : Extremely flammable gas.
H225 : Highly flammable liquid and vapor.
H226 : Flammable liquid and vapor.
H280 : Contains gas under pressure; may explode if heated.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 0000000020500037 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025
69

H411 : Toxic to aquatic life with long lasting effects.
H413 : May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Flam. Gas : Flammable gases
Flam. Liq. : Flammable liquids
Press. Gas : Gases under pressure
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT : UK. Biological monitoring guidance values
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
2019/1831/EU / TWA : Limit Value - eight hours
2019/1831/EU / STEL : Short term exposure limit
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



We create chemistry

PM 2P93 UV Fill-R Grey 0,4L

Version 3.0 Revision Date: 13.10.2025 SDS Number: 0000000020500037 Date of last issue: 23.08.2025
Date of first issue: 31.03.2025
69

of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : Restricted to professional users.
For multi-pack systems observe material safety data sheets of all components.

Classification of the mixture:

Aerosol 1	H222, H229
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN