

B 2A42 PlasticBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2026
4.0	29.05.2026	0000000020500144 20	Date of first issue: 20.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : B 2A42 PlasticBODY 1,5KG

Product code : 000000002050014420

1.2 Relevant identified uses of the substance or mixture and uses advised againstUse of the Sub-
stance/Mixture : Coatings and related products**1.3 Details of the supplier of the safety data sheet****Company:**BASF Coatings France SAS
Z.I de Breuil-Le-Sec, Rue André Pommery
60480 Breuil-Le-Sec
FranceTelephone: +33 3 4477-7777
E-mail address: product-safety-coatings@basf.com**1.4 Emergency telephone**National emergency number:
+27 11 203 2420
International emergency number:
+49 180 2273-112**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.

B 2A42 PlasticBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2026
4.0	29.05.2026	0000000020500144	Date of first issue: 20.02.2023
		20	

Specific target organ toxicity - repeated exposure, Category 1

H372: Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

2.2 Label elements**Labeling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



Signal Word : Danger

Hazard Statements :	H226	Flammable liquid and vapor.
	H304	May be fatal if swallowed and enters airways.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H361d	Suspected of damaging the unborn child.
	H372	Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements :

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist or vapors.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous ingredients which must be listed on the label:

styrene
maleic anhydride

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

B 2A42 PlasticBODY 1,5KG

Version 4.0 Revision Date: 29.05.2026 SDS Number: 0000000020500144 Date of last issue: 12.05.2026
 Date of first issue: 20.02.2023
 20

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

Chemical nature : unsaturated polyester resin
 synthetic polymerizates
 organic compounds
 fillers
 pigment

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
styrene	100-42-5 202-851-5 601-026-00-0 01-2119457861-32-0236 01-2119457861-32-0192 01-2119457861-32-0233	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 (Respiratory system) STOT RE 1; H372 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 12,5 - < 15
maleic anhydride	108-31-6 203-571-6 607-096-00-9	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Respiratory system) specific concentration limit Skin Sens. 1A; H317 >= 0,001 %	>= 0,001 - < 0,1

B 2A42 PlasticBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2026
4.0	29.05.2026	0000000020500144 20	Date of first issue: 20.02.2023

For explanation of abbreviations see section 16.

SECTION 4: First aid measures**4.1 Description of first-aid measures**

- | | |
|-------------------------|---|
| General advice | : In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product.
Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.
Keep patient warm and at rest.
Never give anything by mouth to an unconscious person.
Move out of dangerous area.
Immediately remove contaminated clothing.
First aid personnel should pay attention to their own safety. |
| If inhaled | : If breathed in, move person into fresh air.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician or poison control center immediately. |
| In case of skin contact | : Do NOT use solvents or thinners.
Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
If symptoms persist, call a physician. |
| In case of eye contact | : If easy to do, remove contact lens, if worn.
Call a physician immediately.
Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. |
| If swallowed | : Rinse mouth with water.
Do not induce vomiting due to aspiration hazard.
Keep at rest.
If swallowed, call a poison control center or doctor immediately. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|----------|---|
| Symptoms | : Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. |
| Risks | : When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia. |

B 2A42 PlasticBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2026
4.0	29.05.2026	0000000020500144 20	Date of first issue: 20.02.2023

Risk of product entering the lungs on vomiting after ingestion.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Suspected of damaging the unborn child.

Causes damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.
Treat symptomatically.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Dry powder
Carbon dioxide (CO₂)
Water spray
Foam

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : Cool containers/tanks with water spray.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Avoid breathing vapours.

B 2A42 PlasticBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2026
4.0	29.05.2026	0000000020500144	Date of first issue: 20.02.2023
		20	

For non-emergency personnel:
Use personal protective equipment.
Ensure adequate ventilation, especially in confined areas.
Keep away from sources of ignition.
For emergency responders:
Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
Avoid subsoil penetration.
Do not allow uncontrolled discharge of product into the environment.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Ensure adequate ventilation.

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).
Do not return residues to the storage containers.
Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.
The workplace should be equipped with an emergency shower and eye-rinsing facility.
Avoid contact with the skin, eyes and clothing.
Handle in accordance with good industrial hygiene and safety practice.
Do not breathe vapors or spray mist.

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapors are heavier than air and spread along floors. Vapor forms explosive mixtures with air.

B 2A42 PlasticBODY 1,5KG

Version 4.0 Revision Date: 29.05.2026 SDS Number: 0000000020500144 Date of last issue: 12.05.2026
Date of first issue: 20.02.2023

20

The relevant fire protection measures should be noted. Use explosion-proof equipment.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely.
Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Further information on storage conditions : Keep away from heat. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing. Keep in a dry, cool and well-ventilated place.

Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Recommended storage temperature : 5,00 - 25,00 °C

Packaging material : Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate)

7.3 Specific end use(s)

Specific use(s) : Please refer to the technical leaflet for further information.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
talc	14807-96-6	OEL-RL (respirable dust fraction)	4 mg/m ³	ZA OEL
Further information: Occupational Exposure Limits - Restricted Limits For Hazardous Chemical Agents				
Barium sulfate	7727-43-7	OEL-RL (inhala-ble fraction)	10 mg/m ³	ZA OEL
Further information: Occupational Exposure Limits - Restricted Limits For Hazardous Chemical Agents				
styrene	100-42-5	OEL- ML	40 ppm	ZA OEL
Further information: Occupational Exposure Limits - Maximum Limits For Hazardous Chemical Agents, denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B				
		OEL - ML STEL/C	80 ppm	ZA OEL

B 2A42 PlasticBODY 1,5KG

Version 4.0 Revision Date: 29.05.2026 SDS Number: 0000000020500144 Date of last issue: 12.05.2026
 Date of first issue: 20.02.2023
 20

	Further information: Occupational Exposure Limits - Maximum Limits For Hazardous Chemical Agents, denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B			
Titanium dioxide	13463-67-7	OEL-RL	10 mg/m3	ZA OEL
	Further information: Occupational Exposure Limits - Restricted Limits For Hazardous Chemical Agents, denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B			
maleic anhydride	108-31-6	OEL-RL (inhalable fraction and vapour)	0,02 mg/m3	ZA OEL
	Further information: Occupational Exposure Limits - Restricted Limits For Hazardous Chemical Agents, dermal sensitisation, potential to produce dermal sensitisation, respiratory sensitisation, potential to produce respiratory sensitisation			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
styrene	100-42-5	Mandelic acid and phenylglyoxylic acid: 400 mg/g creatinine (Urine)	End of shift	ZA BEI
		Styrene: 40 µg/l (Urine)	End of shift	ZA BEI

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
talc	Workers	dermal	Long-term systemic effects	43,2 mg/kg
	Workers	dermal	Long-term local effects	4,54 mg/cm2
	Workers	by inhalation	Long-term local effects	3,6 mg/m3
	Workers	by inhalation	Acute systemic effects	2,16 mg/m3
	Workers	by inhalation	Long-term systemic effects	2,16 mg/m3
	Workers	by inhalation	Acute local effects	3,6 mg/m3
Barium sulfate	Workers	Inhalation	Local effects, Systemic effects, Long-term exposure	10 mg/m3
styrene	Workers	Inhalation	Long-term systemic effects	85 mg/m3
	Workers	dermal	Long-term systemic effects	406 mg/kg
	Workers	Inhalation	Acute systemic effects	289 mg/m3
	Workers	Inhalation	Acute local effects	306 mg/m3
Titanium dioxide	Workers	Inhalation	Long-term local ef-	0 - 1,25

B 2A42 PlasticBODY 1,5KG

Version 4.0 Revision Date: 29.05.2026 SDS Number: 0000000020500144 Date of last issue: 12.05.2026
 Date of first issue: 20.02.2023
 20

			fects	mg/m3
	Workers	by inhalation	Long-term local effects	170 µg/m3
	Workers	by inhalation	Long-term local effects	0,8 mg/m3
	Workers	by inhalation	Long-term local effects	1,25 mg/m3
maleic anhydride	Workers	Inhalation	Long-term systemic effects	0,4 mg/m3
	Workers	Inhalation	Acute systemic effects	0,8 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
talc	Air	10 mg/m3
	sediment (freshwater)	31,33 mg/kg
	Sea water	141,26 mg/l
	Fresh water	597,97 mg/l
Barium sulfate	sediment (marine water)	3,13 mg/kg
	Fresh water	0,115 mg/l
	sediment (freshwater)	600,4 mg/kg
	Soil	207,7 mg/kg
styrene	Fresh water	0,028 mg/l
	sediment (freshwater)	0,614 mg/kg
	Soil	0,2 mg/kg
	Sea water	0,0014 mg/l
maleic anhydride	sediment (marine water)	0,307 mg/kg
	sediment (freshwater)	0,334 mg/kg
	sediment (marine water)	0,0334 mg/kg
	Soil	0,0415 mg/kg
	Fresh water	0,1 mg/l
	Sea water	0,01 mg/l

8.2 Exposure controls**Engineering measures**

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Required when there is a risk of eye contact.
 Safety glasses with side-shields conforming to EN166

Hand protection

Remarks

: Wear protective gloves. Any chemical protection glove certified according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers

B 2A42 PlasticBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2026
4.0	29.05.2026	0000000020500144	Date of first issue: 20.02.2023
		20	

- of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)
- Preventive skin protection
- Skin and body protection : Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.
- Anti-static protective clothing
- Respiratory protection : Suitable respiratory equipment:
full face mask with AB2P3 class combination filter
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
- Protective measures : Do not breathe vapour/spray.
Eye wash fountains and safety showers must be easily accessible.
- If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.
- Avoid contact with the skin, eyes and clothing.
Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- Physical state : liquid
- Form : liquid
- Color : gray
- Odor : of styrene
- pH : substance/mixture is non-soluble (in water)
- Melting point/freezing point : not determined

B 2A42 PlasticBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2026
4.0	29.05.2026	0000000020500144	Date of first issue: 20.02.2023
		20	

Boiling point/boiling range	:	139,00 - 149,00 °C
Flash point	:	30 °C Method: ISO 3679
Flammability	:	Flammable liquid and vapour.
Sustained combustibility	:	Sustains combustibility: yes
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	> 35,0 g/m ³
Vapor pressure	:	7,0 hPa (20 °C) 33,0 hPa (50 °C)
Density	:	1,830 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	> 200 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity Viscosity, kinematic	:	411,6 mm ² /s (23 °C) not determined (40 °C)
Flow time	:	> 60 s at 23 °C Cross section: 6 mm Method: ISO 2431
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Self-heating substances	:	The substance or mixture is not classified as self heating.
-------------------------	---	---

B 2A42 PlasticBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2026
4.0	29.05.2026	0000000020500144 20	Date of first issue: 20.02.2023

Metal corrosion rate : Not corrosive to metals.

Particle size : The substance / product is marketed or used in a non solid or granular form.

SECTION 10: Stability and reactivity**10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazardous reactions when stored and handled according to instructions.

10.4 Conditions to avoid

Conditions to avoid : Heat.
Protect from frost.
Heat, flames and sparks.
Avoid direct sunlight.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

B 2A42 PlasticBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2026
4.0	29.05.2026	0000000020500144	Date of first issue: 20.02.2023
		20	

Components:**styrene:**

Acute inhalation toxicity : LC50 (Rat): 12 mg/l
Exposure time: 4 h
Test atmosphere: vapor

maleic anhydride:

Acute oral toxicity : LD50 (Rat): 1.090 mg/kg
Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information**12.1 Toxicity**

No data available

B 2A42 PlasticBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2026
4.0	29.05.2026	0000000020500144	Date of first issue: 20.02.2023
		20	

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential**Components:****styrene:**

Partition coefficient: n-octanol/water	:	log Pow: 2,96 (25 °C)
		Method: OECD Test Guideline 107

maleic anhydride:

Partition coefficient: n-octanol/water	:	log Pow: -2,61 (19,8 °C)
		GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment**Product:**

Assessment	:	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
------------	---	--

12.6 Other adverse effects**Product:**

Endocrine disrupting potential	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Additional ecological information	:	Avoid release to the environment.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC
		Packaging that is not properly emptied must be disposed of as

B 2A42 PlasticBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2026
4.0	29.05.2026	0000000020500144	Date of first issue: 20.02.2023
		20	

the unused product.

Waste Code : 08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

SECTION 14: Transport information**14.1 UN number**

UNRTDG	: UN 1263
IMDG	: UN 1263
IATA	: UN 1263

14.2 UN proper shipping name

UNRTDG	: PAINT
IMDG	: PAINT
IATA	: PAINT

14.3 Transport hazard class(es)

	Class	Subsidiary risks
UNRTDG	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

UNRTDG	
Packing group	: III
Labels	: 3
IMDG	
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
IATA (Cargo)	
Packing instruction (cargo aircraft)	: 366
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable Liquids
IATA (Passenger)	
Packing instruction (passenger aircraft)	: 355
Packing instruction (LQ)	: Y344
Packing group	: III

B 2A42 PlasticBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2026
4.0	29.05.2026	0000000020500144	Date of first issue: 20.02.2023
		20	

Labels : Flammable liquid

14.5 Environmental hazards**UNRTDG**

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks : ADR: Packages smaller than or equal to 450 liters, not goods/merchandise of Class 3
IMDG: Packages smaller than or equal to 450 liters, not goods/merchandise of Class 3

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59) : Number on list 75

Regulation (EU) No 2024/590 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Volatile organic compounds (VOC) content: 210 g/l
VOC content excluding water

Directive 2010/75/EU of 24 November 2010 on industrial and

B 2A42 PlasticBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2026
4.0	29.05.2026	0000000020500144	Date of first issue: 20.02.2023
		20	

livestock rearing emissions (integrated pollution prevention and control)

Volatile organic compounds (VOC) content: 14,42 %

Other regulations:

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information**Full text of H-Statements**

H226	: Flammable liquid and vapor.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H361d	: Suspected of damaging the unborn child.
H372	: Causes damage to organs through prolonged or repeated exposure.
H373	: Causes damage to organs through prolonged or repeated exposure if inhaled.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Resp. Sens.	: Respiratory sensitization
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation

B 2A42 PlasticBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2026
4.0	29.05.2026	0000000020500144	Date of first issue: 20.02.2023
		20	

Skin Sens.	:	Skin sensitization
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
ZA BEI	:	South Africa. The Regulations for Hazardous Chemical Agents, Biological Exposure Indices
ZA OEL	:	South Africa. The Regulations for Hazardous Chemical Agents, Occupational Exposure Limits
ZA OEL / OEL- ML	:	Occupational Exposure Limit Maximum limit - 8- hour exposure or equivalent (12 hour shifts).
ZA OEL / OEL - ML STEL/C	:	Occupational Exposure Limit Maximum limit - Short term occupational exposure limits / ceiling limits
ZA OEL / OEL-RL	:	Occupational Exposure Limit Restricted limit - 8- hour exposure or equivalent (12 hour shifts)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : For multi-pack systems observe material safety data sheets of all components.

B 2A42 PlasticBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: 12.05.2026
4.0	29.05.2026	0000000020500144	Date of first issue: 20.02.2023
		20	

Restricted to professional users.

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Repr. 2	H361d
STOT RE 1	H372
Asp. Tox. 1	H304

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

ZA / EN