

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
		35	

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : B 2A16C PerformBODY 1,5KG

Product code : 000000002050014535

1.2 Relevant identified uses of the substance or mixture and uses advised againstUse of the Sub-
stance/Mixture : Putty**1.3 Details of the supplier of the safety data sheet****Company:**BASF Coatings France SAS
Z.I de Breuil-Le-Sec, Rue André Pommery
60480 Breuil-Le-Sec
FranceTelephone: +33 3 4477-7777
E-mail address: product-safety-coatings@basf.com**1.4 Emergency telephone**National emergency number:
+27 11 203 2420
International emergency number:
+49 180 2273-112**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - repeated	H372: Causes damage to organs through pro-

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
		35	

exposure, Category 1

longed or repeated exposure.

2.2 Label elements**Labeling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



Signal Word : Danger

Hazard Statements	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H319	Causes serious eye irritation.
	H361d	Suspected of damaging the unborn child.
	H372	Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements :

Prevention:

P201	Obtain special instructions before use.
P260	Do not breathe dust.
P264	Wash skin thoroughly after handling.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.

Hazardous ingredients which must be listed on the label:

styrene
maleic anhydride**Additional Labeling**

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
35			

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**

Chemical nature : organic compounds
organic solvent
inorganic compounds
fillers
pigment
unsaturated polyester resin

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
styrene	100-42-5 202-851-5 601-026-00-0 01-2119457861-32-0236 01-2119457861-32-0192 01-2119457861-32-0233	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Repr. 2; H361d STOT SE 3; H335 (Respiratory system) STOT RE 1; H372 (Auditory system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 15 - < 20
ethyl acetate	141-78-6 205-500-4 607-022-00-5	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	>= 1 - < 2
maleic anhydride	108-31-6 203-571-6 607-096-00-9	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Respiratory system)	>= 0,001 - < 0,1

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
		35	

		specific concentration limit Skin Sens. 1A; H317 ≥ 0,001 %	
--	--	---	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures**4.1 Description of first-aid measures**

- | | | |
|-------------------------|---|---|
| General advice | : | First aid personnel should pay attention to their own safety.
If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).
Immediately remove contaminated clothing.
In all cases of doubt, or when symptoms persist, seek medical attention.
Move out of dangerous area.
Never give anything by mouth to an unconscious person. |
| If inhaled | : | If symptoms persist, call a physician.
If breathed in, move person into fresh air.
If breathing is irregular or stopped, administer artificial respiration. |
| In case of skin contact | : | If symptoms persist, call a physician.
Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Do NOT use solvents or thinners. |
| In case of eye contact | : | Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
Call a physician immediately.
If easy to do, remove contact lens, if worn. |
| If swallowed | : | If symptoms persist, call a physician.
Do NOT induce vomiting.
Rinse mouth. |

4.2 Most important symptoms and effects, both acute and delayed

- | | | |
|----------|---|---|
| Symptoms | : | Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. |
|----------|---|---|

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
		35	

Risks : Dusts may cause mechanical irritation to eyes.

Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Suspected of damaging the unborn child.
Causes damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No known specific antidote.
Treat symptomatically.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media : Water spray
Dry powder
Foam
Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Fire will produce dense black smoke containing hazardous combustion products (see section 10).

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Appropriate breathing apparatus may be required.

Further information : Cool containers/tanks with water spray.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Personal precautions : Avoid breathing dust.
For non-emergency personnel:
Use personal protective equipment.
Ensure adequate ventilation, especially in confined areas.

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
		35	

Keep away from sources of ignition.
For emergency responders:
Advice on product handling can be found in sections 7 and 8
of this safety data sheet.

6.2 Environmental precautions

Environmental precautions : Do not allow uncontrolled discharge of product into the environment.
Avoid subsoil penetration.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Avoid dust formation.
Contain and collect mechanically and dispose of in accordance with local regulations.
Ensure adequate ventilation.

6.4 Reference to other sections

For disposal considerations see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Advice on safe handling : Provide good ventilation of working area (local exhaust ventilation if necessary).
Do not return residues to the storage containers.
Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws.
The workplace should be equipped with an emergency shower and eye-rinsing facility.
Avoid contact with the skin, eyes and clothing.
Handle in accordance with good industrial hygiene and safety practice.
Protect from moisture.
Avoid creating dust.

Advice on protection against fire and explosion : Avoid all sources of ignition: heat, sparks, open flame. The relevant fire protection measures should be noted. Avoid dust formation.

Hygiene measures : Remove contaminated clothing immediately and dispose of safely.
Wash hands before breaks and at the end of workday. Keep away from food, drink and animal feedingstuffs.

B 2A16C PerformBODY 1,5KG

Version 1.0 Revision Date: 03.07.2026 SDS Number: 0000000020500145 Date of last issue: -
 Date of first issue: 03.07.2026
 35

7.2 Conditions for safe storage, including any incompatibilities

- Further information on storage conditions : Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Protect from moisture. Keep in a dry, cool and well-ventilated place.
- Advice on common storage : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Packaging material : Suitable material: Carbon steel (Iron), tinned carbon steel (Tinplate), Galvanized carbon steel (Zinc)

7.3 Specific end use(s)

- Specific use(s) : Please refer to the technical leaflet for further information.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
talc	14807-96-6	OEL-RL (respirable dust fraction)	4 mg/m ³	ZA OEL
Further information: Occupational Exposure Limits - Restricted Limits For Hazardous Chemical Agents				
styrene	100-42-5	OEL- ML	40 ppm	ZA OEL
Further information: Occupational Exposure Limits - Maximum Limits For Hazardous Chemical Agents, denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B				
		OEL - ML STEL/C	80 ppm	ZA OEL
Further information: Occupational Exposure Limits - Maximum Limits For Hazardous Chemical Agents, denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B				
Titanium dioxide	13463-67-7	OEL-RL	10 mg/m ³	ZA OEL
Further information: Occupational Exposure Limits - Restricted Limits For Hazardous Chemical Agents, denotes carcinogenicity, which is based on GHS categorisation, including category 1A, 1B				
ethyl acetate	141-78-6	TWA	200 ppm 734 mg/m ³	2017/164/EU
Further information: Indicative				
		STEL	400 ppm 1.468 mg/m ³	2017/164/EU
Further information: Indicative				
		OEL-RL	800 ppm	ZA OEL

B 2A16C PerformBODY 1,5KG

Version 1.0 Revision Date: 03.07.2026 SDS Number: 0000000020500145 Date of last issue: -
 Date of first issue: 03.07.2026
 35

Further information: Occupational Exposure Limits - Restricted Limits For Hazardous Chemical Agents				
		TWA	200 ppm 734 mg/m ³	2017/164/EU
		STEL	400 ppm 1.468 mg/m ³	2017/164/EU
maleic anhydride	108-31-6	OEL-RL (inhalable fraction and vapour)	0,02 mg/m ³	ZA OEL
Further information: Occupational Exposure Limits - Restricted Limits For Hazardous Chemical Agents, dermal sensitisation, potential to produce dermal sensitisation, respiratory sensitisation, potential to produce respiratory sensitisation				

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
styrene	100-42-5	Mandelic acid and phenylglyoxylic acid: 400 mg/g creatinine (Urine)	End of shift	ZA BEI
		Styrene: 40 µg/l (Urine)	End of shift	ZA BEI

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
talc	Workers	Dermal	Long-term systemic effects	43,2 mg/kg
	Workers	Dermal	Long-term local effects	4,54 mg/cm ²
	Workers	Inhalation	Long-term local effects	3,6 mg/m ³
	Workers	Inhalation	Acute systemic effects	2,16 mg/m ³
	Workers	Inhalation	Long-term systemic effects	2,16 mg/m ³
	Workers	Inhalation	Acute local effects	3,6 mg/m ³
styrene	Workers	Inhalation	Long-term systemic effects	85 mg/m ³
	Workers	Dermal	Long-term systemic effects	406 mg/kg
	Workers	Inhalation	Acute systemic effects	289 mg/m ³
Titanium dioxide	Workers	Inhalation	Acute local effects	306 mg/m ³
	Workers	Inhalation	Long-term local effects	0 - 1,25 mg/m ³
	Workers	Inhalation	Long-term local effects	170 µg/m ³

B 2A16C PerformBODY 1,5KG

Version 1.0 Revision Date: 03.07.2026 SDS Number: 0000000020500145 Date of last issue: -
 Date of first issue: 03.07.2026
 35

	Workers	Inhalation	Long-term local effects	0,8 mg/m3
	Workers	Inhalation	Long-term local effects	1,25 mg/m3
ethyl acetate	Workers	Inhalation	Local effects, Systemic effects, Long-term exposure	734 mg/m3
	Workers	Dermal	Long-term systemic effects	63 mg/kg
	Workers	Inhalation	Local effects, Systemic effects, Short-term exposure	1468 mg/m3
maleic anhydride	Workers	Inhalation	Long-term systemic effects	0,4 mg/m3
	Workers	Inhalation	Acute systemic effects	0,8 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006

Substance name	Environmental Compartment	Value
talc	Air	10 mg/m3
	sediment (freshwater)	31,33 mg/kg
	Sea water	141,26 mg/l
	Fresh water	597,97 mg/l
	sediment (marine water)	3,13 mg/kg
styrene	Fresh water	0,028 mg/l
	sediment (freshwater)	0,614 mg/kg
	Soil	0,2 mg/kg
	Sea water	0,0014 mg/l
	sediment (marine water)	0,307 mg/kg
ethyl acetate	Fresh water	0,24 mg/l
	Sea water	0,024 mg/l
	sediment (freshwater)	1,15 mg/kg
	sediment (marine water)	0,115 mg/kg
	Soil	0,148 mg/kg
maleic anhydride	sediment (freshwater)	0,334 mg/kg
	sediment (marine water)	0,0334 mg/kg
	Soil	0,0415 mg/kg
	Fresh water	0,1 mg/l
	Sea water	0,01 mg/l

8.2 Exposure controls**Engineering measures**

Ensure adequate ventilation.

Personal protective equipment

Eye/face protection : Required when there is a risk of eye contact.
 tight-fitting protective goggles with face screen

Hand protection : Wear protective gloves. Any chemical protection glove certi-

Remarks :

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
35			

- fied according to EN ISO 374-1 is suitable: e.g. butyl rubber gloves - material thickness: 0.5 mm Further information on penetration time is available from the manufacturer of the glove. Data are based on information from the glove manufacturer, the raw material manufacturer or according to specifics of the product components. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Request information on glove permeation properties from the glove supplier. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): Suitable materials against splashes (recommended: At least protective index 1, corresponding > 10 minutes of permeation time according to EN ISO 374-1)
- Preventive skin protection
- Skin and body protection : Care should be taken in the selection of protective clothing to ensure that inflammation of the skin at neck and wrists through contact with the powder is avoided.
disposable coveralls
Personnel should wear antistatic, flame-retardant clothing made of natural fibres and/or heat-resistant synthetic fibres.
- Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Wear respiratory protection if ventilation is inadequate.
- Protective measures : Eye wash fountains and safety showers must be easily accessible.
- If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn.
- Avoid contact with the skin, eyes and clothing.
Handle in accordance with good industrial hygiene and safety practice.
Avoid breathing dust.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Physical state : solid

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
		35	

Form	:	paste
Color	:	beige
Odor	:	characteristic
pH	:	substance/mixture is non-soluble (in water)
Melting point/freezing point	:	not determined
Boiling point/boiling range	:	Study technically not feasible.
Flash point	:	Not applicable
Evaporation rate	:	not determined
Flammability	:	Will not burn
Sustained combustibility	:	Sustains combustibility: no Measurement method: UN Manual of Tests and Criteria: Test L.2
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Vapor pressure	:	The product is a non-volatile solid.
Relative vapor density	:	The product is a non-volatile solid.
Relative density	:	No data available
Density	:	1,754 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	not determined
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	427 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity Viscosity, kinematic	:	411,6 mm ² /s (23 °C)

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
		35	

not determined (40 °C)

Flow time : > 60 s at 23 °C
Cross section: 6 mm
Method: ISO 2431

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Self-heating substances : The substance or mixture is not classified as self heating.

Metal corrosion rate : Not corrosive to metals.

Particle size : No data available

SECTION 10: Stability and reactivity**10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Dust can form an explosive mixture in air.

10.4 Conditions to avoid

Conditions to avoid : Avoid direct sunlight.
Avoid dust formation.

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
		35	

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Components:**styrene:**

Acute inhalation toxicity : LC50 (Rat): 12 mg/l
Exposure time: 4 h
Test atmosphere: vapor

maleic anhydride:

Acute oral toxicity : LD50 (Rat): 1.090 mg/kg
Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Skin corrosion/irritation

Causes skin irritation.

Components:**ethyl acetate:**

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
		35	

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1 Toxicity**

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential**Components:****styrene:**

Partition coefficient: n-octanol/water	:	log Pow: 2,96 (25 °C)
		Method: OECD Test Guideline 107

ethyl acetate:

Partition coefficient: n-octanol/water	:	log Pow: 0,68 (25 °C)
		pH: 7
		GLP: no

maleic anhydride:

Partition coefficient: n-octanol/water	:	log Pow: -2,61 (19,8 °C)
		GLP: yes

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment**Product:**

Assessment	:	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of
------------	---	--

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
		35	

0.1% or higher.

12.6 Other adverse effects**Product:**

Endocrine disrupting potential	:	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Additional ecological information	:	Avoid release to the environment.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Product	:	Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.
Contaminated packaging	:	Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC Packaging that is not properly emptied must be disposed of as the unused product.
Waste Code	:	08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

SECTION 14: Transport information**14.1 UN number**

UNRTDG	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.2 UN proper shipping name

UNRTDG	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.3 Transport hazard class(es)

UNRTDG	:	Not regulated as a dangerous good
--------	---	-----------------------------------

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
		35	

IMDG : Not regulated as a dangerous good

IATA : Not regulated as a dangerous good

14.4 Packing group

UNRTDG : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the following entries should be considered: Number on list 75
REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59).	:	Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	:	Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	Not applicable
---	----------------

Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control)
		Volatile organic compounds (VOC) content: 17,1 %
		Volatile organic compounds (VOC) content: 299,93 g/l

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
35			

VOC content excluding water

Other regulations:

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

Assessment of safe use has been performed for the mixture and the result is documented in section 7 and 8 of the SDS

SECTION 16: Other information**Full text of H-Statements**

H225	: Highly flammable liquid and vapor.
H226	: Flammable liquid and vapor.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H361d	: Suspected of damaging the unborn child.
H372	: Causes damage to organs through prolonged or repeated exposure.
H372	: Causes damage to organs through prolonged or repeated exposure if inhaled.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Resp. Sens.	: Respiratory sensitization
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
35			

Skin Sens.	: Skin sensitization
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2017/164/EU	: Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
ZA BEI	: South Africa. The Regulations for Hazardous Chemical Agents, Biological Exposure Indices
ZA OEL	: South Africa. The Regulations for Hazardous Chemical Agents, Occupational Exposure Limits
2017/164/EU / STEL	: Short term exposure limit
2017/164/EU / TWA	: Limit Value - eight hours
ZA OEL / OEL- ML	: Occupational Exposure Limit Maximum limit - 8- hour exposure or equivalent (12 hour shifts).
ZA OEL / OEL - ML STEL/C	: Occupational Exposure Limit Maximum limit - Short term occupational exposure limits / ceiling limits
ZA OEL / OEL-RL	: Occupational Exposure Limit Restricted limit - 8- hour exposure or equivalent (12 hour shifts)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

B 2A16C PerformBODY 1,5KG

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.07.2026	0000000020500145	Date of first issue: 03.07.2026
		35	

Further information

Other information : For multi-pack systems observe material safety data sheets of all components.
Restricted to professional users.

Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Repr. 2	H361d
STOT RE 1	H372

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

ZA / EN